



# ADHESIVES

## General Information/Technical Data Sheet



# AlbaChem® Premium Mist Adhesive

AlbaChem Premium Mist Adhesive is used to provide a temporary tack or permanent bond on a wide variety of substrates. It may be used to bond cloth, wood, film, plastic, cardboard and more. Premium Mist Adhesive sprays in a coarse mist pattern, to yield a strong tack with a low overspray. A great all purpose pallet adhesive for screen printing, Premium Mist can also be used in embroidery and cutting rooms.

### Packaging:

Item# 1787 Aerosol Can Net Wt. 14 oz (397 grams)  
Case Pack: 12

### Advantages:

- Super Strong Tack
- Stable at High Temperatures
- Less Frequent Re-application
- Does not contain any chlorinated solvents.
- Great for Screen Printing Applications.

### Safety:

- Does not contain chlorinated solvents
- Requires less frequent applications, reducing amount of adhesive adhesive used in the workplace

### Directions for use:

Shake well before using. Make sure surfaces to be bonded are clean and dry. Hold can 6 to 8 inches from surface to be sprayed. Use a sweeping motion when spraying. For a temporary bond, spray Premium Mist onto one of the surfaces to be bonding only. Allow a few seconds for product to dry before putting the surfaces together. For a permanent bond, spray onto both surfaces that are being bonded. Immediately put the surfaces together, while the adhesive is still wet. To avoid clogging, after using, turn can upside down and spray against a piece of paper until a clean stream of air flows.

### Environmental Benefits:

- Contains under 65% (by weight) of V.O.C.'s and complies with CARB VOC's standards.
- Does not contain vinyl acetate or other toxic adhesives
- Product is stable and non-reactive under normal conditions of use, storage and transport.
- Meets the exception requirements for shipping as a limited quantity.

### Technical Data:

Appearance:	Cloudy/White	<b>HMIS HAZARD RATING:</b>	
Odor:	Solvent	Health:	1 (Slight)
Shelf Life:	> 1 Year	Flammability:	4 (High)
Flashpoint:	-156°F (propellant)	Physical Hazard:	2 (Moderate)
		Personal Protection:	B (Gloves & Eye Protection)
VOC's:	<65% (by weight) Specific	UN Number:	1950
Gravity:	0.6543 (estimated)	Packaging Exemption:	Limited Quantity
			NOT for sale in California



Wilcox Graphic Supplies  
Phone: 1 800 561 8844